

1. Home
2. Products
3. Product catalogue
4. General products (21X.00) - 01/01/2023



VIMAR



Enclosures and mounting boxes: Flush-mount box 4M f/hollow walls blue

V71704

Enclosures and mounting boxes / Flush mounting boxes / For hollow walls

Flush-mount box 4M f/hollow walls blue

4-module mounting frame (GW 850 °C) for hollow walls, light blue

- Suitable for several types of hollow walls (e.g. plasterboard, wood, plastic laminate or similar)
- Preparation of the hole with a hollow cutter with a diameter of 68 mm. Hole centring plate incorporated into the back
- Improved retention knockouts, designed for the insertion of pipes with various cross-sections (16, 20 or 25 mm) and metal fins for surface mounting the box on walls with a variable thickness of between 1 and 38 mm
- Fixing lugs for support screws made of metal
- Wide range of accessories available: accessories with a template function for tracing the hole, with joining function for mounting in series and installation on the inside of the wall; internal partitions; decorative covers




Product Status

3 - Active


Minimum order quantity

5 NR

You may also be interested in



V71634 - Flat cover 4M




V71574 - Accessory for 4M boxes for hollow walls

Video

- Tutorial ISOBOX EN

Drawings



Technical data

- **Class group:** Connection devices
 - **Class:** Box/housing for built-in mounting in the wall/ceiling
 - **Mounting method:** Hollow wall
 - **Shape:** Rectangular
 - **Construction type:** Device connection box (round/square)
 - **Model:** Other
 - **Provided with revolving ring:** No
 - **Connectable:** Yes
 - **Equipped with:** None
 - **Diameter:** 0 mm
 - **Length:** 72,50 mm
 - **Width:** 133,80 mm
 - **Depth:** 0,00 - 50,00 mm
 - **Internal depth:** 50,00 mm
 - **For number of electric fittings:** 4
 - **Mounting switching equipment:** Screwing
 - **With screws:** No
 - **Housing feed-through by break-out opening:** Yes
 - **Housing feed-through by seal membrane:** No
 - **Housing feed-through by nozzle:** No
 - **Housing feed-through by step membrane:** No
 - **For tube diameter:** 20/25 mm
 - **Pipe locking:** No
- **Pipe locking optional:** No
 - **Inlet from the rear:** Yes
 - **Number of inlets:** 14
 - **Number of included spouts:** 0
 - **Material:** Plastic
 - **Halogen free:** Yes
 - **Surface protection:** Untreated
 - **Colour:** Blue
 - **Degree of protection (IP):** IP00
 - **Cover model:** None
 - **Transparent cover:** No
 - **Cover attachment:** Screwed
 - **Sealable:** No
 - **Circuit integrity:** None
 - **With screening:** No
 - **Air tight:** No
 - **Max. conductor cross section:** 0
 - **Number of poles of the clamp:** 0
 - **Clamp position fixed:** No
 - **Luminaire hook mounting:** No
 - **Nozzle:** None
 - **With nail lugs:** No
 - **Special application:** None

Certifications

- 00. CE Marking - EU
 - 01. IMQ - Italy (download)
 - 15. CCC - China (download)
- 37. Marking - Morocco
 - 43. UKCA mark - Great Britain
 - 96. Electrotechnical expert (download)

Packaging

		
8 007352 425705	8 007352 425712	8 007352 425729
Code	Code	Code
Quantity	Quantity	Quantity
Dim.	Dim.	Dim.
Weight	Weight	Weight
1 NR	5 NR	110 NR
13.4x7.2x5 [cm]	13.4x7.2x25 [cm]	59x38.5x30 [cm]
38.64 [g]	193.2 [g]	5,090 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).

