



Eikon Next: 5V 2,1A USB supply unit 2M Next

20295.N

Eikon Next / Devices / USB power units

5V 2,1A USB supply unit 2M Next

5 V 2,1 A power supply unit for electronic devices, 2 USB ports supply a total of 2,1 A suitable for recharging a 2,1 A single device (e.g. tablet) or two 1 A devices simultaneously (e.g. smartphone and phablet), supply voltage 120-230 V~ 50/60 Hz, Next - 2 modules

Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [pdf Prese USB \(391 kb\)](#)
- [Multilanguage instructions sheet \(1186 kb\)](#)


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Domestic switching devices
- **Class:** USB power supply
- **Model:** Bus
- **Number of outputs:** 2
- **Operating voltage:** 12000 - 23000 v
- **Frequency:** 50 - 60 HZ
- **Max. output current:** 2.100 mA
- **Output voltage:** 5 v
- **Mounting method:** Flush mounted (plaster)
- **Colour:** Silver
- **RAL-number:** 0

Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 19. NOM - Mexico
- 35. RCM - Australia ([download](#))
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



8 007352 538917

Code 8007352538917
Quantity 1 NR
Dim. 6x5.4x5.3 [cm]
Weight 67.6 [g]



8 007352 538924

Code 8007352538924
Quantity 10 NR
Dim. 28.1x13.1x6 [cm]
Weight 756 [g]



8 007352 641556

Code 8007352641556
Quantity 120 NR
Dim. 38.5x29x30 [cm]
Weight 9,552 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).