



Eikon Next: A+C-USB supply unit 5V 2,4A 1M Next

20292.AC.N

Eikon Next / Devices / USB power units

A+C-USB supply unit 5V 2,4A 1M Next

5 V 2,4 A USB power supply unit for electronic devices, 1 A-USB and C-USB ports providing a total of 2,4 A for charging simultaneously two devices (e.g. tablet, smartphone), supply voltage 120-240 V~ 50/60 Hz, Next - 1 module

- The type C USB socket outlet is a standard used in latest-generation devices; since it is reversible, it can be inserted either way round
- Compact A+C socket outlets in a single module, 2 types of output for a total power of 2.4 A (divided over the 2 outputs)



Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(787 kb\)](#)


Drawings



Space view



Backside view



3D View


Technical data

- **Class group:** Domestic switching devices
- **Class:** USB power supply
- **Model:** Bus
- **Mounting method:** Flush mounted (plaster)
- **Colour:** Silver
- **RAL-number:** 0

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352643758
Quantity 1 NR
Dim. 6x2.8x5.3 [cm]
Weight 41.2 [g]



Code 8007352643765
Quantity 10 NR
Dim. 14.4x13.1x6 [cm]
Weight 460.8 [g]



Code 8007352686748
Quantity 200 NR
Dim. 50.5x20x28 [cm]
Weight 7,050 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).